



BIXIT Button Camera

MANUAL



Product Features

- 1080p HD Resolution with Audio
- 120° Laser Cut Glass Lens
- Records Audio & Video
- Up to 2.5-Hour Battery Life
- Stores 200 Hours on 128 GB
- Accepts MicroSD Card | 90 Min Per 1GB
- Receive Motion Detection Alerts on Your Smartphone
- Connects to your WiFi or Creates a WiFi hotspot
- Boots-up And Records Automatically

Included



BIXIT Micro Camera, Instruction Manual, Data & Charging USB Cable

Product Design



Getting Started

Charging

Please use the included USB cable to charge the battery. Connect the cable to a USB A/C adpter or any computer port.

Power ON/OFF

Slide the ON/OFF button to ON position. OFF is towards the top of the camera, ON towards the bottom.

Camera Reset

Resetting the camera device to factory default will fix most issues. When the camera is on, use a pin to press and hold the hidden pinhole **reset button** for 5 seconds, the camera will restart with factory settings.

Camera & phone application setup

I. Camera Operation Modes

Red light is the power indicator, which comes up for a few seconds on when the power is on. **Blue** light is WIFI indicator.

Wifi indicator modes:

1. Point-to-point mode: **Blue** light flashes slowly

2. Configuration of remote camera completed: **Blue** light is always on

Note: If you are not clear what mode it is active, reset the camera and switch to point-to-point mode.

This reset works only when the blue light is always on or flashes slowly. Press the Reset key for about 5 seconds until all the indicators go out, and let go until the camera starts (about 30 seconds).

The first time using the camera, the Red light may stay on. Run reset porceidure to reset.

II.Download APP software



Method 1.

Scan the QR code (Figure 1), and enter the download page (Figure 2). Choose to download the software according to the system of the mobile phone. Download and install the computer client through the download address:

http://lookcam.ffvv.xyz:8800/lookcam_download.html

Method 2. Search for APP software called LOOKCAM on Google Play, or the App Store, download and install it.

Note: If you scan with WeChat, when (Figure 2) appears, click the browser in sharing in the upper right corner to open and download the software.

After downloading and installing, find the LookCam app on your smartphone



III. Point-to-point (phone to camera device connection)

Enter the mobile phone WI-FI settings, find the WiFi account (UID number) and connect. As shown in the figure

Settings WLAN					
	WLAN				
~	B000534CBMXR Unsecured Network		? ()		
СН	IOOSE A NETWORK				
	AFOUNDRY		? (]		
	AFOUNDRY-5.8G	•	∻ ()		
	ChinaNet-C3PX	•	∻ (i)		
	ChinaNet-d73X	٩	२ (i)		
	ChinaNet-MLM2	•	२ ()		

After the UID of the device is connected, open the phone APP (LOOKCAM). (As shown below)



Click Cancel point-to-point short-range viewing (point-to-point is connected and viewing allowed) and click Yes to pair router and enter remote viewing (If you need to set up remote, please continue to read the instructions and follow the steps)



IV.Set up the camera for remote connection

When point-to-point video can be viewed, return to the previous menu and enter the interface as shown in the picture.

Click the setup icon \rightarrow Advanced Configuration \rightarrow WiFi Connection Configuration \rightarrow Find WiFi \rightarrow Enter Password \rightarrow Click OK and the camera will restart automatically. (Wait for the camera to restart (about 40 seconds). The camera will change from offline to online, at which time the viewable video can be accessed remotely.)

	My Dev	ice	•		My Device	÷ (+)
	B000534CBMX B000534CBMXR Device Online	R	¢		B000534CBMXR B000534CBMXR Connecting	¢
					B000534CBM	XR
					Edit Device	9
					Delete Devic	e
					Reconnect De	vice
				[Config Wi-I	=i
Q Video	Photo	Files	() More		Cancel	



WiFi Setting

n	ected WiFi	
		Not connect
D	list	
	EW1300	>
	ChinaNet-x67f	>
	clsw	>
	AFOUNDRY	>
	ChinaNet-TwFU	>
	chuanglan-mi	>
	ChinaNet-C3PX	>
	TP-LINK_C4A1	>
	ChinaNet-MLM2	>
	MEETING	>
	DAKXY	>



Note: When connecting remotely, make sure you enter the correct WIFI password. Otherwise, the camera will restart automatically after clicking OK. However, due to the wrong password, the camera will not be online, and then you would need to reset it and re-pair.

Quick Troubleshooter

Check memory card:

The camera supports up to 128 GB Micro SD card. Please use High Speed Class 10 FAT formatted memory card. You must format the Micro SD before using. If SD card is not recognized when inserted into the camera, simply remove and re-insert.

Camera offline:

- 1. Check power
- 2. Check if your router is working properly.
- 3. Weak Wi-Fi signal.
- 4. Wrong password wrong while Wi-Fi setting

Glitchy or stuttering video playback:

You should choose a suitable resolution to watch according to your internet speed. Internet connection interruption will also cause video to freeze.

Forgot password or password invalid:

Press and hold the reset button for 10 seconds to restore the camera device to the factory settings.

The initial password for each camera is 123456. Please change the password to ensure the security of your camera.

If the camera cannot be connected to the router, please reset, and connect the hot spots before completing the configuration.

Camera Device Specifications

Resolution Ratio	1080P/720P/640P/320P		
Video Format	AVI		
Frame Rate	25 FPS		
Viewing Angle	150 degree horizontally /90 vertically		
Motion detection activation dstance	Straight line, 6 meters		
Minimal Illumination	1LUX		
Video Duration	Over 1 Hours		
Video Encoder	H.264		
Recording Range	5m ²		
Current Consumption	380MA/3.7V		
Storage Temperature	-20-80 degree centigrade		
Operating Temperature	-10-60 degree centigrade		
Operation Humidity	15-85%RH		
Memory Card Type	TF card, MicroSD Card		
Player Software	VLCPlayer/SMPlayer		
Computer Operating System	Windows/Mac OS X		
Mobile Phone Operating System	Android/iOS		
Web browser	IE7 and above, chrome, firefox safari.etc		
Maximum Users	4		